



GUS
DEVELOPING THE FUTURE
EMPOWERING WOMEN



BIO-TORQ LD100

Application for the effective degradation of solid waste in pit toilets and septic tanks

In nature, all animal and vegetable matter, from insects to mighty oaks, is broken down and recycled into plant food by enzymes and bacteria. BIO-TORQ LD100 uses this same principle to degrade animal and vegetable waste. Like all living things, bacteria must eat to survive. Fortunately, certain types of bacteria will use grease, hair, soap film and all the organic waste for food.

BIO-TORQ LD100 is a blend of bacteria and enzymes. The bacteria are natural, not genetically engineered. The enzyme concentration is the most powerful on the market. BIO-TORQ LD100 is a proprietary blend of superior aerobic (not less than $8 \times 10^8/g$) and anaerobic (not less than $7, 8 \times 10^8/g$) bacteria selected for their ability to degrade organic waste.

PRODUCT CHARACTERISTICS

- Bacteria Counts: Aerobic bacteria not less than $8 \times 10^8/g$: Anaerobic bacteria not less than $7, 8 \times 10^8/g$
- Heavy Metals: Less than 50ppm
- Aflatoxins: Absent
- Antibiotic Activity: Absent
- E. Coli: Absent in 01.g
- Appearance: Tan, low dusting powder on a cereal/salt base
- Packaging: 100 gram sachets, 25kg bags
- Solubility: >80% in H₂O
- pH: 5,0 – 8,5
Effluent with a pH outside this range should be pre-treated with a suitable acid or lime prior to dosing with BIO-TORQ LD100
- Temperature: Up to 50°C

Safety:

BIO-TORQ LD100 is non-toxic. It creates no heat, no fumes, no boiling. It does not attack live tissue or inorganic materials, only organic wastes like grease, hair, food particles, paper, cotton and sewage. This makes BIO-TORQ LD100 safe for people, plumbing and the environment. BIO-TORQ LD100 changes the waste particles into water, carbon dioxide and mineral ash which run harmlessly out of your waste system. These elements are then available for plant life.

Effectiveness:

Within minutes after pouring the bacteria into the affected area, the bacteria begin to eat their way into the waste that has accumulated. This is their natural food. They digest the waste and spread throughout your system, cleaning it completely.

Economical:

- Eliminates the need to clean grease traps and cable drains
- Eliminates the need to buy dangerous chemicals
- Eliminates the need to buy deodorant blocks (urinals)
- Eliminates costly compensation to employees that have been injured by using dangerous chemicals

Multipurpose application:

- Residential and commercial applications
- All drain and sewer pipes, including:
 - Bath tubs
 - Cat Litter Boxes
 - Floor drains
 - Garbage disposal odours
 - Grease traps
 - Kitchen sinks
 - Laundry drains
 - Lavatories
 - Lift Stations
 - Outdoor outhouses and cesspools
 - Pit toilets (long-drops) or (poof-doofs)
 - RV & boat holding tanks
 - Septic tanks and drain fields
 - Sewage ejector sumps
 - Showers

Dosage:

The following dosages are merely a guideline.

1. INDUSTRIAL & COMMERCIAL

Area	Initial Dose Rate	Regular Maintenance Rate
Septic Tanks (Pit Toilets/Grease Traps)	100g per week	100g per month
Industrial Effluent (e.g. abattoir)	1% for 3 days (w/w)	0,3% per day (w/w)
Agricultural Waste	4% once off (w/w)	1% weekly (w/w)

2. SEWAGE PLANT

Area	Initial Dose Rate	Regular Maintenance Rate
Trickling Filter	0,1% once off (w/w)	0,05% weekly (w/w)
Anaerobic Digester	1% for 3 days (w/w)	1% weekly (w/w)
Oxidation Pond	1% for 3 days (w/w)	1% weekly (w/w)
Activated Sludge	1% for 3 days (w/w)	1% weekly (w/w)

How to use BIO-TORQ LD100:

Bio-Enzymes act like short order cooks. They prepare food for bacteria by breaking large molecules down into a size the bacteria can "eat." Each works on one specific type of molecule. For example, the protease enzyme only works on protein. Lipase works only on fats. The bacteria in BIO-TORQ LD100 are dormant while in the container. When exposed to or mixed with water they come to life in few minutes. In the meantime, the enzymes are breaking down the waste. They act very fast. In fact, they work on contact. When the bacteria revive, they are hungry. Each one eats its weight of waste every minute - and they never sleep! As a result of eating and growing they start to multiply through cell division. Their numbers will double rapidly under favourable conditions.

In the treatment of drains, for example BIO-TORQ LD100 should be mixed with warm (not hot) water and applied when no water will be drained for six to eight hours. This allows some of the bacteria time to embed them into the waste so they won't be washed out when water is drained again.

Periodic maintenance treatment prevents new organic waste build-up, so no more slow drains or clogs!

Application Explanation

Septic Systems

Most septic systems in operation do not function well. The tanks need pumping frequently because of solids build up. All too often the fields stop absorbing water prematurely. The number one reason is the vast array of household chemicals which either inhibit or kill biological action. The coliform bacteria normally present in sewage are in no way equal to present daily demands. They are used to warm body temperatures and are poor enzyme producers. They cannot handle synthetic materials present in detergents even under the best conditions.

BIO-TORQ LD100 contains not only potent enzymes, but also bacteria that outperform the coliform species in very important ways. They are high producers of enzymes and they are acclimated so that they feed on a larger variety of materials in the waste such

as fats and grease, vegetable oil, paper, detergents, fabric softeners, aliphatic and aromatic organic compounds as well as synthetic organics.

Chemicals, bleaches, detergents, food preservatives and bowl cleaners inhibit or kill bacterial action within your septic system. This lets solids accumulate in the tank, some of which flow out and clog the drain field. **BIO-TORQ LD100** will restore the necessary bacterial action and make your system work at full efficiency! People on a septic system must select their cleaning products very carefully.

Do not use chemical cleaners in conjunction with **BIO-TORQ LD100**

Garbage Disposal Systems

Odours come from waste that sticks to the disposal wall and slowly moulds and rots. It is hurled there by the high-speed rotating blades.

By using **BIO-TORQ LD100**, the waste will be quickly digested by the live cultures, thus eliminating the odour.

Grease Traps

Cleaning out a grease trap is the worst of jobs in a food service operation. After the horrible odorous muck is removed it still has to be disposed of. Unfortunately, we are running out of landfills to put it in.

BIO-TORQ LD100 will digest the grease, eliminating the unwanted task, as well as the disposal of the pollutant.

The grease trap must be large enough to accomplish two things. The flow of the water through the trap must be 1) slowed and 2) cooled, so that the oils and fats can rise and be retained between the baffles while the water continues on down the sewer

A garbage disposal should never discharge into a grease trap.

If these criteria are met, daily treatment of the pot sink will maintain the digestive action.

Eliminating the need to pump the trap offers significant cost saving.

Sumps with Pumps

When ground water accumulates in sumps, odours may be noticeable. This is especially true if household or sanitary waste is present.

BIO-TORQ LD100 eliminates the odour by quickly digesting organic material in the waste water.

Pumps will require less energy when the rotor, housing and lines are free of build-up.

Lower energy costs and longer pump life are added bonuses.

Pit Toilets (Long-Drops)

Mention a pit-toilet and the first thing that pops to mind is odour, flies and maggots.

BIO-TORQ LD100 turns the waste into water and carbon dioxide very quickly.

This dramatically reduces odour and flies, and without flies there are no maggots.

Cleaning and disposal of the pit become easier and it is more pleasant for the user.

Filling of the pit toilet is significantly prolonged and percolation into the underground is contaminant free.

RV and Boat Holding Tanks

As the waste water level increases in the tank, some scum adheres to the sides and sensor. When the tank is drained, more scum is deposited. With continued use, this coating becomes odorous. It is additional weight and reduces tank capacity. There is no large access to the tanks, and the build-up is often so great, and clean-up so difficult and time consuming, that replacing the tank is often less expensive.

RVers using chemicals in their tank are also encountering the new problem of not being able to dispose of their chemically treated waste at many dump stations. Wastewater treatment plants do not want this chemical toxicity in their plants, so they charge dump stations large fines.

If **BIO-TORQ LD100** is used from the beginning, a tank will drain cleanly, including the sensor, if there is one.

Using **BIO-TORQ LD100** in a tank previously treated with chemicals will take larger doses and some time to overcome the toxicity. It will, however, remove the old build-up.

Waste from tanks treated with **BIO-TORQ LD100** is accepted anywhere because it is biologically active.

Safety:

- BIO-TORQ LD100 is an environmentally friendly, safe-to-use product that contains a non-GMO strain of Bacillus Subtilis spore and various Enzymes derived from this organism, for example Bacterial A-Amylase and Proteases.
- No product specific certification is provided for, however, the strain for the active ingredients is non-pathogenic and the enzymes are produced by standard fermentation techniques and conform to Generally Recognized as Safe (GRAS) status and have FDA approval for Foodstuff applications.
- The preparation conforms to FAO/WHO and FCC recommended standards.
- In the event of an accidental spillage, wash the affected area with water.

Storage:

To maintain maximum activity of the enzymes and the viability of the bacteria, BIO-TORQ LD100 should be stored under cool, dry conditions, at temperatures less than 25°C.

Inactivation of BIO-TORQ LD100:

Bacteria / Enzymes present in BIO-TORQ LD100 will tolerate temperatures up to 70°C. However, the bacteria in the product cannot tolerate temperatures in excess of 50°C. High concentrations of heavy metals will inhibit the activity of the product. Common cleaning agents containing chlorine (bleaches) and quaternary ammonium compounds (disinfectants) etc. can have a detrimental effect on the product. Neutralisation of these inhibitors is necessary before treatment with BIO-TORQ LD100.

The information contained in this leaflet is to the best of our knowledge, true & accurate, but any recommendations or suggestions which may be made are without guarantee since the conditions of use are beyond our control. No license or immunity under any patents is granted or implied. Eco Distribution Africa does not guarantee that the above products can be used as described without prior positive testing or the use of these products does not infringe third parties' patent rights.



082 967 1539



office@gusolutions.co.za



www.gusolutions.co.za



Suite MW 105
Private Bag X1838
Middelburg, 1050, MP